

## **Xcel<sup>®</sup>ent<sup>™</sup>**

## The XCELLENT ASSURE ST-2

is a semi-steel special trailer tire. It is dedicated to be designed with low rolling resistance and fuel economy. XCELLENT ASSURE ST-2 Radial Trailer tire can meet every requirement of your trailer demand. The full range of tires are manufactured with two full nylon cap (except 13") and reinforced polyester. ST235/85R16 is especially designed with three ply polyester for highest loading capacity. All skus are traditional design with full tread depth and wider footprint, enables the tire's high speed performance and long mileage.

## **Features & Benefits**

- Full tread depth and inner high tensile steel belts guarantee maximum treadwear.
- Special tread compound offers greater power, durability, wet grip handling.
- Engineered excellently for trailer applications.
- Reinforced structure ensures high loading capacity and safety.










2-PLY Polyester Construction (ST235/85R16 with 3-PLY Polyester)









made in Thailand

## **SPECIFICATIONS**

SIZE	LOAD INDEX	SPEED RATING	PLY RATING	TREAD DEPTH (32NDS)	STANDARD RIM (INCH)	SECTION WIDTH (INCH)	OVERALL DIAMETER (INCH)	MAX LOAD(LBS)	MAX PRESSURE (PSI)
ST175/80R13	97/93	М	8/D	9.4	5.00	7.0	24.0	1610/1430	65
ST205/75R14	105/101	М	8/D	10.3	5.50	8.0	26.1	2040/1820	65
ST215/75R14	108/103	М	8/D	10.3	6.00	8.5	26.7	2200/1930	65
ST205/75R15	107/102	М	8/D	10.3	5.50	8.0	27.1	2150/1870	65
ST205/75R15	111/106	М	10/E	10.3	5.50	8.0	27.1	2400/2090	80
ST225/75R15	113/108	М	8/D	10.3	6.00	8.8	28.3	2540/2200	65
ST225/75R15	117/112	М	10/E	10.3	6.00	8.8	28.3	2830/2470	80
ST235/80R16	124/120	М	10/E	10.3	6.00	9.3	30.8	3520/3080	80
ST235/85R16	128/124	М	12/F	10.0	6.50	9.3	31.7	3960/3520	95